



Performance Materials

**SAFETY DATA SHEET**

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1

Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries  
 40210

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS\_NL

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries

UFI: ANG0-00X4-K00M-774G

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Recommended use : Reserved for industrial and professional use.

Restrictions on use Consumer use

**1.3 Details of the supplier of the safety data sheet**

Alta Performance Materials Hispania S.L.U  
 Carretera Reial 137-139  
 08960 Sant Just Desvern - Barcelona  
 Spain  
 +34 93 206 51 20 (in Spain)

sds.composites@altapm.com

**1.4 Emergency telephone number**

001-800-424-9300/001-703-527-3887, or contact your local emergency telephone number at 030 274 88 88. Exclusively for medical professionals in case of acute poisoning.

**Regulatory Information Number**

+34 93 206 51 20 (in Spain), or contact your local CSR contact person

**Product Information**

+34 93 206 51 20 (in Spain)

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 3

H226: Flammable liquid and vapour.

Skin irritation, Category 2

H315: Causes skin irritation.

Eye irritation, Category 2

H319: Causes serious eye irritation.



Performance Materials

**SAFETY DATA SHEET**

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1

Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries  
 40210

Reproductive toxicity, Category 2

H361d: Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated exposure, Category 1

H372: Causes damage to organs through prolonged or repeated exposure.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H361d Suspected of damaging the unborn child.  
 H372 Causes damage to organs through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P260 Do not breathe mist or vapours.  
 P264 Wash skin thoroughly after handling.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P370 + P378 In case of fire: Use dry sand, dry chemical or



Performance Materials

## SAFETY DATA SHEET

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1

Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries  
 40210

alcohol-resistant foam to extinguish.

### Hazardous components which must be listed on the label:

Styrene

Precautionary statements : **Keep dust/air mixtures away from ignition sources.**

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Styrene	100-42-5 202-851-5 601-026-00-0 01-2119457861-32-xxxx	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 40 - < 50
methacrylic acid	79-41-4	Acute Tox. 4; H302	>= 0,5 - < 1



Performance Materials

**SAFETY DATA SHEET**

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1

Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries  
 40210

	201-204-4 607-088-00-5 01-2119463884-26-xxxx	Acute Tox. 4; H332 Acute Tox. 3; H311 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system)	
		specific concentration limit STOT SE 3; H335 ≥ 1 %	

For explanation of abbreviations see section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- General advice : Move out of dangerous area.  
 Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
 IF INHALED: Call a POISON CENTER/ doctor if you feel unwell.  
 Keep patient warm and at rest.  
 If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
 If on skin, rinse well with water.  
 Wash contaminated clothing before re-use.  
 If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
 Remove contact lenses.  
 Protect unharmed eye.



Performance Materials

## SAFETY DATA SHEET

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1

Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries  
 40210

If swallowed : Do NOT induce vomiting.  
 Rinse mouth.

Obtain medical attention.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
 stomach or intestinal upset (nausea, vomiting, diarrhea)  
 irritation (nose, throat, airways)  
 confusion

Risks : Causes skin irritation.  
 Causes serious eye irritation.  
 May cause respiratory irritation.  
 Suspected of damaging the unborn child.  
 Causes damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 Water spray  
 Foam  
 Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical

Unsuitable extinguishing media : High volume water jet



Performance Materials

## SAFETY DATA SHEET

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1

Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries  
 40210

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Organic dusts at sufficient concentration can form explosive mixtures in air.  
 Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.  
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
 Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
 Carbon monoxide  
 Burning produces noxious and toxic fumes.  
 Hydrocarbons

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Do not use a solid water stream as it may scatter and spread fire.  
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
 Use a water spray to cool fully closed containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ventilate the area.  
 Evacuate personnel to safe areas.  
 Remove all sources of ignition.  
 Use personal protective equipment.  
 Ensure adequate ventilation.  
 Beware of vapours accumulating to form explosive



Performance Materials

## SAFETY DATA SHEET

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1

Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries  
 40210

concentrations. Vapours can accumulate in low areas. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Comply with all applicable federal, state, and local regulations. Suppress (knock down) gases/vapours/mists with a water spray jet.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Use only in area provided with appropriate exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. During spraying, wear suitable respiratory equipment.

Open drum carefully as content may be under pressure. Avoid formation of aerosol. Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe vapours/dust. Do not smoke. Container hazardous when empty. Take precautionary measures against static discharges. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited in the



Performance Materials

## SAFETY DATA SHEET

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1

Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries  
 40210

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national regulations.

Secondary operations, such as grinding and sanding, may produce dust.

Maintain good housekeeping. Do not permit dust layers to accumulate, for example, on floors, ledges, and equipment, in order to avoid any potential for dust explosion hazards.

Advice on protection against fire and explosion

: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). No sparking tools should be used. Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment.

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. No smoking.

Further information on storage conditions

: Keep locked up or in an area accessible only to qualified or authorised persons.

Other data

: No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s)

: No data available





Performance Materials

**SAFETY DATA SHEET**

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1


Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries  
 40210

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

Contains no substances with occupational exposure limit values.

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

Styrene : End Use: Workers  
 Exposure routes: Inhalation  
 Potential health effects: Short-term exposure, Systemic effects  
 Value: 289 mg/m3  
 End Use: Workers  
 Exposure routes: Inhalation  
 Potential health effects: Short-term exposure, Local effects  
 Value: 306 mg/m3  
 End Use: Workers  
 Exposure routes: Inhalation  
 Potential health effects: Long-term exposure, Systemic effects  
 Value: 85 mg/m3  
 End Use: Workers  
 Exposure routes: Skin contact  
 Potential health effects: Long-term exposure, Systemic effects  
 Value: 406 mg/kg  
 End Use: Consumers  
 Exposure routes: Inhalation  
 Potential health effects: Short-term exposure, Systemic effects  
 Value: 174,25 mg/m3  
 End Use: Consumers  
 Exposure routes: Inhalation  
 Potential health effects: Short-term exposure, Local effects  
 Value: 182,75 mg/m3  
 End Use: Consumers  
 Exposure routes: Skin contact  
 Potential health effects: Long-term exposure, Systemic effects  
 Value: 343 mg/kg  
 End Use: Consumers  
 Exposure routes: Ingestion  
 Potential health effects: Long-term exposure, Systemic effects  
 Value: 2,1 mg/kg  
 End Use: Consumers  
 Exposure routes: Inhalation  
 Potential health effects: Long-term exposure, Systemic effects  
 Value: 10,2 mg/m3

 <p><b>ALTA</b> Performance Materials</p>		Page: 10
<b>SAFETY DATA SHEET</b>		Revision Date: 11.07.2025
		Print Date: 20.11.2025
		SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210		Version: 7.1

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Styrene : Fresh water  
Value: 0,028 mg/l  
Fresh water  
Value: 0,04 mg/l  
Intermittent use/release

Marine water  
Value: 0,014 mg/l  
Sewage treatment plant  
Value: 5 mg/l  
Fresh water sediment  
Value: 0,614 mg/kg  
Marine sediment  
Value: 0,307 mg/kg  
Soil  
Value: 0,2 mg/kg

## 8.2 Exposure controls


### Engineering measures

Prevent unauthorised persons entering the zone.  
Maintain air concentrations below occupational exposure standards.  
All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.  
Minimize open handling.  
Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., drip-less quick connections).  
Use closed processing systems or containment technologies to control at source (e.g., glove boxes/isolators) and to prevent leakage of compounds into the workplace.  
Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.  
Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.  
Provide appropriate exhaust ventilation at places where dust is formed.

### Personal protective equipment

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Use eye protection according to EN 166.

 <p><b>ALTA</b> Performance Materials</p>		Page: 11
<b>SAFETY DATA SHEET</b>		Revision Date: 11.07.2025
		Print Date: 20.11.2025
		SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210		Version: 7.1

#### Hand protection

Material : Laminate (Barrier© or Silvershield©)  
Break through time : 480 min  
Glove thickness : > 0,5 mm

#### Remarks

: The exact break through time can be obtained from the protective glove producer and this has to be observed. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

#### Skin and body protection

: Wear as appropriate:  
Impervious clothing  
Safety shoes  
Flame-resistant clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Discard gloves that show tears, pinholes, or signs of wear.  
  
Protective clothing complying with EN 13688.  
Safety shoes complying with EN ISO 20345.

#### Respiratory protection


: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Wear respiratory equipment when entering the spray area. In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.

In the case of vapour formation use a respirator with an approved filter.

#### Filter type

: Organic vapour type (A)

Respiratory protection complying with EN 136.  
Respiratory protection complying with EN 140.  
Respiratory protection complying with EN 14387.

 <p><b>Performance Materials</b></p>		Page: 12
<b>SAFETY DATA SHEET</b>		Revision Date: 11.07.2025
		Print Date: 20.11.2025
		SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210		Version: 7.1

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: light yellow
Odour	: aromatic
Odour Threshold	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flammability	: May form combustible dust concentrations in air (during processing).
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Flash point	: 29,4 °C Method: Seta closed cup
Decomposition temperature	: No data available
pH	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20,5 mm <sup>2</sup> /s (40 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available



Performance Materials

## SAFETY DATA SHEET

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1

Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries  
 40210

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

Relative density : No data available

Density : 1,0433 g/cm<sup>3</sup> (25 °C)

Relative vapour density : > 1  
(Air = 1.0)

### 9.2 Other information

Oxidizing properties : No data available

Self-ignition : No data available

Evaporation rate : < 1  
Ethyl Ether = 1

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability


Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation may occur.  
 Vapours may form explosive mixture with air.  
 This product does not present a dust explosion hazard as delivered. However, fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source, is a potential dust explosion hazard.

### 10.4 Conditions to avoid

Conditions to avoid : excessive heat  
 Exposure to air.  
 Exposure to sunlight.

 <p><b>ALTA</b> Performance Materials</p>		Page: 14
<b>SAFETY DATA SHEET</b>		Revision Date: 11.07.2025
		Print Date: 20.11.2025
		SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210		Version: 7.1

Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Acids  
aluminum  
aluminum chloride  
Bases  
Copper  
Copper alloys  
halogens  
iron chloride  
metal salts  
Oxidizing agents  
Peroxides

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Hydrocarbons  
Acetone

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion


#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

 <p><b>Performance Materials</b></p>		Page: 15
<b>SAFETY DATA SHEET</b>		Revision Date: 11.07.2025
		Print Date: 20.11.2025
		SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210		Version: 7.1

Method: Calculation method

**Components:**

**Styrene:**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11,8 mg/l, 2770 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

No observed adverse effect level (Humans): 100 ppm  
Exposure time: 7 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

**methacrylic acid:**

Acute oral toxicity : LD50 (Mouse): 1.250 mg/kg  
  
LD50 (Rat, male): 1.320 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 7,1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: The component/mixture is classified as acute inhalation toxicity, category 4., The component/mixture is moderately toxic after short term inhalation.


Acute dermal toxicity : LD50 (Rabbit): 500 - 1.000 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks : May cause skin irritation and/or dermatitis.

 <p><b>ALTA</b> Performance Materials</p>	Page: 16
<b>SAFETY DATA SHEET</b>	Revision Date: 11.07.2025
	Print Date: 20.11.2025
	SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210	Version: 7.1

Result : Repeated exposure may cause skin dryness or cracking.

**Components:**

**Styrene:**

Species : Rabbit  
Result : Irritating to skin.

Species : human skin  
Result : No skin irritation

**methacrylic acid:**

Method : OECD Test Guideline 404  
Result : Corrosive after 3 minutes or less of exposure

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.  
Causes serious eye irritation.

**Components:**

**Styrene:**

Result : Irritating to eyes.  
Remarks : Vapour during processing may be irritating to the respiratory tract and to the eyes.

**methacrylic acid:**

Result : Corrosive

**Respiratory or skin sensitisation**


**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.



 <p><b>ALTA</b> Performance Materials</p>		Page: 17
<b>SAFETY DATA SHEET</b>		Revision Date: 11.07.2025
		Print Date: 20.11.2025
		SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210		Version: 7.1

### **Components:**

#### **Styrene:**

Exposure routes : Skin contact  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Result : negative

Exposure routes : inhalation (vapour)  
Species : Humans  
Assessment : Does not cause respiratory sensitisation.  
Result : negative

#### **methacrylic acid:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Did not cause sensitisation on laboratory animals.  
Method : OECD Test Guideline 406

#### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**


#### **methacrylic acid:**

Genotoxicity in vitro : Test Type: Ames test  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 487  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian bone marrow sister chromatid exchange  
Species: Rat (male)  
Cell type: Bone marrow  
Method: OECD Test Guideline 475  
Result: negative

Species: Mouse (male)  
Method: OECD Test Guideline 478  
Result: negative

 <p><b>ALTA</b> Performance Materials</p>		Page: 18
<b>SAFETY DATA SHEET</b>		Revision Date: 11.07.2025
		Print Date: 20.11.2025
		SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210		Version: 7.1

Test Type: Micronucleus test  
Species: Mouse (male)  
Cell type: peripheral blood cells  
Method: OECD Test Guideline 474  
Result: negative

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Suspected of damaging the unborn child.

#### **Components:**

##### **Styrene:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

##### **methacrylic acid:**

Effects on fertility : Species: Rat  
Application Route: Oral  
Fertility: NOAEL Mating/Fertility: 400 mg/kg body weight  
Symptoms: No effects on fertility, No effects on reproduction parameters  
Method: OECD Test Guideline 416

Effects on foetal development : Species: Rabbit  
Application Route: Oral  
Developmental Toxicity: NOAEL F1: 450 mg/kg body weight  
Symptoms: No specific developmental abnormalities  
Method: OECD Test Guideline 414


#### **STOT - single exposure**

May cause respiratory irritation.

#### **Components:**

##### **Styrene:**

Assessment : May cause respiratory irritation.

 <p><b>ALTA</b> Performance Materials</p>	Page: 19
<b>SAFETY DATA SHEET</b>	Revision Date: 11.07.2025
	Print Date: 20.11.2025
	SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210	Version: 7.1

#### **methacrylic acid:**

Exposure routes : Inhalation  
Target Organs : Respiratory Tract  
Assessment : May cause respiratory irritation.

#### **STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

#### **Components:**

##### **Styrene:**

Exposure routes : inhalation (vapour)  
Target Organs : Auditory system  
Assessment : Causes damage to organs through prolonged or repeated exposure.

#### **Repeated dose toxicity**

#### **Components:**

##### **Styrene:**

Species : Human  
: 20 mg/l  
Application Route : inhalation (vapour)  
Target Organs : Auditory system (hearing)


Species : Human  
NOAEL : 615 mg/kg  
Application Route : Skin contact

#### **methacrylic acid:**

Species : Rat, male and female  
: 352 mg/m3  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 90 Days  
Control Group : yes  
Symptoms : Local irritation, Reduced body weight

#### **Aspiration toxicity**

Not classified based on available information.

 <p><b>ALTA</b> Performance Materials</p>		Page: 20
<b>SAFETY DATA SHEET</b>		Revision Date: 11.07.2025
		Print Date: 20.11.2025
		SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210		Version: 7.1

### Components:

#### **Styrene:**

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **Further information**

#### Product:

Remarks : Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:


#### **Styrene:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4,02 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,7 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 4,9 mg/l  
Exposure time: 72 h

EC10 (Pseudokirchneriella subcapitata (green algae)): 0,28 mg/l

 <p><b>Performance Materials</b></p>		Page: 21
<b>SAFETY DATA SHEET</b>		Revision Date: 11.07.2025
		Print Date: 20.11.2025
		SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210		Version: 7.1

Exposure time: 96 h

Toxicity to microorganisms : EC50 (activated sludge): ca. 500 mg/l  
Exposure time: 0,5 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,01 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

Toxicity to soil dwelling organisms : NOEC: 34 mg/kg  
Exposure time: 14 d  
Species: Eisenia fetida (earthworms)  
Method: OECD Test Guideline 207

**methacrylic acid:**


Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 85 mg/l  
Exposure time: 96 h  
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 130 mg/l  
Exposure time: 48 h  
Test Type: flow-through test

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 20 mg/l  
End point: Biomass  
Exposure time: 72 h  
Test Type: flow-through test  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l  
Exposure time: 35 d  
Species: Danio rerio (zebra fish)  
Test Type: flow-through test  
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 53 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: flow-through test  
Method: OECD Test Guideline 211

 <p><b>ALTA</b> Performance Materials</p>	Page: 22
<b>SAFETY DATA SHEET</b>	Revision Date: 11.07.2025
	Print Date: 20.11.2025
	SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210	Version: 7.1

## 12.2 Persistence and degradability

### Components:

#### **Styrene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 60 %  
Exposure time: 10 d

#### **methacrylic acid:**

Biodegradability : Inoculum: activated sludge  
Result: Readily biodegradable.  
Biodegradation: 87 %  
Exposure time: 28 d

## 12.3 Bioaccumulative potential

### Components:

#### **Styrene:**

Bioaccumulation : Bioconcentration factor (BCF): < 100

Partition coefficient: n-octanol/water : log Pow: 2,96 (25 °C)

#### **methacrylic acid:**

Bioaccumulation : Bioconcentration factor (BCF): 1,0  
Remarks: Bioaccumulation is unlikely.


Partition coefficient: n-octanol/water : log Pow: 0,93

## 12.4 Mobility in soil

### Components:

#### **Styrene:**

Distribution among environmental compartments : Koc: 352

 <p><b>ALTA</b> Performance Materials</p>	Page: 23
<b>SAFETY DATA SHEET</b>	Revision Date: 11.07.2025
	Print Date: 20.11.2025
	SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210	Version: 7.1

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### Components:

#### **Styrene:**

Assessment : Substance is not persistent, bioaccumulative, and toxic (PBT).. Substance is not very persistent and very bioaccumulative (vPvB).

#### **methacrylic acid:**

Assessment : Substance is not persistent, bioaccumulative, and toxic (PBT).. Substance is not very persistent and very bioaccumulative (vPvB).

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



Performance Materials

Page: 24

## SAFETY DATA SHEET

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1

Derakane Momentum™ 411-350 epoxy vinyl ester resin  
™ Trademark, ALTA its subsidiaries, registered in various countries  
40210

**Product** : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

**Contaminated packaging** : Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

**ADN:** UN1866

**ADR:** UN1866

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:** UN1866

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** UN1866

**INTERNATIONAL MARITIME DANGEROUS GOODS:** UN1866

**RID:** UN1866

#### 14.2 UN proper shipping name

**ADN:** RESIN SOLUTION

**ADR:** RESIN SOLUTION

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:** Resin solution

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** Resin solution

**INTERNATIONAL MARITIME DANGEROUS GOODS:** RESIN SOLUTION

**RID:** RESIN SOLUTION

#### 14.3 Transport hazard class(es)

**ADN:** 3

**ADR:** 3

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:** 3


**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** 3

**INTERNATIONAL MARITIME DANGEROUS GOODS:** 3

**RID:** 3

#### 14.4 Packing group



 <p><b>ALTA</b> Performance Materials</p>	Page: 25
<b>SAFETY DATA SHEET</b>	Revision Date: 11.07.2025
	Print Date: 20.11.2025
	SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210	Version: 7.1

**ADN:** III

**ADR:** III

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:** III

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** III

**INTERNATIONAL MARITIME DANGEROUS GOODS:** III

**RID:** III

#### 14.5 Environmental hazards

**ADN:** Not applicable

**ADR:** Not applicable

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:** Not applicable

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** Not applicable

**INTERNATIONAL MARITIME DANGEROUS GOODS:** Not applicable

**RID:** Not applicable

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to IMO instruments

Ship Type: Not applicable

Hazard code(s): Not applicable

Pollutant Category: Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.


### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

 <p><b>Performance Materials</b></p>	Page: 26
<b>SAFETY DATA SHEET</b>	Revision Date: 11.07.2025
	Print Date: 20.11.2025
	SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210	Version: 7.1

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
(75, 3)  
Styrene  
  
4-tert-butylpyrocatechol  
  
toluene  
(48)  
2,2' -Oxybisethanol  
  
benzene  
(72, 5, 29, 28)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c	FLAMMABLE LIQUIDS	Quantity 1 5.000 t	Quantity 2 50.000 t
-----	-------------------	-----------------------	------------------------

General Assessment Methodology (GAM)

Aquatic harmfulness : B2 Toxic for aquatic organisms.


Abatement effort : B Readily biodegradable aquatic harmful substances.

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment). styrene

**The components of this product are reported in the following inventories:**

TCSI : On the inventory, or in compliance with the inventory

TSCA On or in compliance with the active portion of the TSCA inventory

 <p><b>Performance Materials</b></p>	Page: 27
<b>SAFETY DATA SHEET</b>	Revision Date: 11.07.2025
	Print Date: 20.11.2025
	SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210	Version: 7.1

AIIC	On the inventory, or in compliance with the inventory
DSL	This product contains one or several components that are not on the Canadian DSL and have annual quantity limits.
ENCS	Not in compliance with the inventory
ISHL	Not in compliance with the inventory
KECI	On the inventory, or in compliance with the inventory
PICCS	Not in compliance with the inventory
IECSC	On the inventory, or in compliance with the inventory
NZIoC	Not in compliance with the inventory
AICS	On the inventory, or in compliance with the inventory

#### Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

#### 15.2 Chemical safety assessment

No data available

### SECTION 16: Other information

#### Further information

Revision Date: 11.07.2025

#### Classification procedure:

H226	Flammable liquid and vapour.	Based on product data or assessment
H315	Causes skin irritation.	Calculation method
H319	Causes serious eye irritation.	Calculation method



**Performance Materials**

## SAFETY DATA SHEET

Revision Date: 11.07.2025

Print Date: 20.11.2025

SDS Number: R0402382

Version: 7.1

Derakane Momentum™ 411-350 epoxy vinyl ester resin  
 ™ Trademark, ALTA its subsidiaries, registered in various countries  
 40210


H361d	Suspected of damaging the unborn child.	Calculation method
H335	May cause respiratory irritation.	Calculation method
H372	Causes damage to organs through prolonged or repeated exposure.	Calculation method
H412	Harmful to aquatic life with long lasting effects.	Calculation method

### Full text of H-Statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by ALTA's Environmental Health and Safety Department (+34 93 206 51 20 (in Spain)).

Sources of key data used to compile the Safety Data Sheet  
 ALTA internal data including own and sponsored test reports  
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

 <p><b>ALTA</b> Performance Materials</p>	Page: 29
<b>SAFETY DATA SHEET</b>	Revision Date: 11.07.2025
	Print Date: 20.11.2025
	SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210	Version: 7.1

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

GAM : Water Hazard Class for the Netherlands

ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP : Classification, Labelling and Packaging

CSA : Chemical Safety Assessment

CSR : Chemical Safety Report


DNEL : Derived No Effect Level.

EINECS : European Inventory of Existing Commercial Chemical Substances.

ELINCS : European List of Notified Chemical Substances

GV: Exposure limits (DK)

PEC : Predicted Effect Concentration

 <p><b>ALTA</b> Performance Materials</p>		Page: 30
<b>SAFETY DATA SHEET</b>		Revision Date: 11.07.2025
		Print Date: 20.11.2025
		SDS Number: R0402382
Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, ALTA its subsidiaries, registered in various countries 40210		Version: 7.1

PEL : Permissible Exposure Limits  
 PNEC : Predicted No Effect Concentration  
 REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals  
 RID : Regulation Concerning the International Transport of Dangerous Goods by Rail  
 WGK : German Water Hazard Class  
 NL / EN