

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Chemical name/ trade name: **Hardener HG 356**
UFI: CDVV-K0Q5-200M-PXP7
Producer: **GRM Systems s.r.o.**
Address: **Olomouc, 77900, Technologická 886/28**
Distributor: **GRM Systems s.r.o.**
Address: **Olomouc, 77900, Technologická 886/28**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Intended use: Hardener for epoxy resin.
Uses advised against: The product must not be used in ways other than those listed in section 1.

1.3 Details of the supplier of the safety data sheet

Supplier of SDS: GRM Systems s.r.o.
Address: Olomouc, 77900, Technologická 886/28
Identification No.: 26916835
Tel: +420 585 431 734
www: <http://www.grm-systems.cz/>
Responsible person for this SDS: Anna Šťáhelová

1.4 Emergency telephone number

Toxicological Information Centre: City Hospital, Dudley Rd, Birmingham, United Kingdom, Tel.: +44 121 507 4123, 844 892 0111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to the EC Regulation No. 1272/2008 (CLP):

Chronic (long term) aquatic hazard, category 3, H412 Harmful to aquatic life with long lasting effects.
Serious eye damage, category 1, H318 Causes serious eye damage.
Skin corrosion, category 1, H314 Causes severe skin burns and eye damage.
Skin sensitisation, category 1, H317 May cause an allergic skin reaction.
Acute Toxicity, category 4, H302 Harmful if swallowed.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]:

Hazard pictogram(s):



Signal word(s): DANGER

Contain: 3-aminomethyl-3,5,5-trimethylcyclohexylamine, Benzyl alcohol

Hazard statement(s):

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

Precautionary statement(s):

P260 Do not breathe vapors.
P264 Wash hands thoroughly with soap after handling.
P280 Wear protective gloves / protective clothing / eye protection.
P301/330/331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303/361/353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305/351/338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Call a physician immediately.
P405 Store locked up.
P501 Dispose of contents / container according to the instructions in the safety data sheet section 13.

Supplemental information:

2.3 Other hazards

This mixture does not contain any substances which are classified as PBT or vPvB
This product does not contain SVHC.
This product does not contain endocrine disruptors in a concentration of 0.1% by weight or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Name of the component	Content (weight %)	CAS EINECS Index N° Reg. Number	Classification according to Regulation (EC) No 1278/2008 (CLP)	
3-aminomethyl-3,5,5-trimethylcyclohexylamine	40-50	2855-13-2 220-666-8 612-067-00-9 01-2119514687-32-0000	Acute Tox. 4 Acute Tox. 4 Aquatic Chronic 3 Skin Corr. 1B Skin Sens. 1	H312 H302 H412 H314 H317
Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	40-50	9046-10-0 618-561-0 01-2119557899-12-0000		
Benzyl alcohol	10-15	100-51-6 202-859-9 603-057-00-5 01-2119492630-38-0000	Acute Tox. 4 Acute Tox. 4	H332 H302

For full text of H-statements see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice:

In case of accident or if you feel unwell, seek medical advice immediately (show the safety data sheet or label if possible).

Inhalation:

Pause exposure. Move the affected person to fresh air quickly and for your own safety, do not let him walk! · Depending on the situation, it is recommended to rinse the oral cavity or nose with water · Change the victim if the substance is affected by clothing · Secure the victim against colds · Call an ambulance if necessary · or provide medical treatment due to the need for further monitoring for at least 24 hours.

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

Skin contact:	Take off contaminated clothing. Wash the affected area with plenty of lukewarm water. If there is no skin injury, it is advisable to use soap, soap solution or shampoo. Seek medical attention.
Eye contact:	Immediately flush eyes with running water, keep eyelids open (even by force); if the affected person has contact lenses, remove them immediately. Rinse for 10-30 minutes from the inner corner to the outer one so that the other eye is not affected. Never neutralize! Depending on the situation, call an ambulance or arrange for medical treatment as soon as possible. Everyone must be sent for examination, even in the event of a small impact.
Ingestion:	DO NOT INDUCE VOMITING! There is a risk of perforation of the esophagus and stomach! IMMEDIATELY RINSE MOUTH WITH WATER AND DRINK 2-5 dl of cold water to reduce the thermal effect of the caustic. Due to the almost immediate effect on the mucous membranes, it is better to give tap water quickly and not delay in finding chilled liquids - with every minute of delay, the condition of the mucosa is irreparably damaged! Sodium or mineral water from which carbon dioxide gas may be released are not suitable. The affected person must not be forced to drink, especially if he already has pain in his mouth or throat. In this case, only allow the victim to rinse the mouth with water. DO NOT SUBMIT ACTIVATED CARBON! (blackening makes it more difficult to examine the condition of the mucous membranes of the digestive tract and has no beneficial effect on acids and alkalis). Do not give anything by mouth if the victim is unconscious or has convulsions. Depending on the situation, call an ambulance or get medical attention as soon as possible.
Protection of first aiders:	When providing first aid, it is necessary to ensure the safety of the rescuer and the rescued.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Foam, extinguishing powder, CO₂, water mist.
Unsuitable extinguishing media: Direct water flow - could cause fire to spread.

5.2 Special hazards arising from the substance or mixture

Combustion products and hazardous gases: smoke, carbon monoxide, carbon dioxide.

5.3 Advice for firefighters

Respiratory units exposed to smoke or vapors must be equipped with respiratory and eye protection devices. When using in enclosed areas, an insulating respirator must be used. Containers exposed to fire cool with water mist. Collect extinguishing water separately, and avoid its penetration into the soil and water. Chemical protective clothing (EN 469).

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing, replace contaminated clothing. Avoid contact with skin and eyes, contamination of clothes and shoes. Ensure ventilation of the affected area. All persons who do not participate in rescue operations to a safe distance.

6.2 Environmental precautions

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

Prevent leakage into the environment, avoid ingress into surface water and sewers, soil and land. In case of leakage into the sewage system or water course, inform immediately its administrator, the police, the fire brigade or the environmental department.

6.3 Methods and material for containment and cleaning up

In case of leakage, localize and, if possible, absorb / remove mechanically. Residues or smaller amounts sweep / get absorbed into a suitable absorbent (universal sorbent, diatomaceous earth, soil, sand) and place in suitable containers and labeled for disposal transmit in accordance with applicable regulations.

6.4 Reference to other sections

See section 7, 8 a 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Use appropriate PPE. Use only in well-ventilated areas

7.2 Conditions for safe storage, including any incompatibilities

Store in well sealed original containers in dry, cool and well-ventilated areas. Store in a vertical position to prevent leakage and dripping. Keep away from food, feed and medication.

7.3 Specific end use(s)

See section 1.2.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Exposure limits: According to national legislation of target country.

Substance	CAS	Permissible exposure limits (mg/m ³)	Maximum permissible concentration (mg/m ³)	Note
Benzyl-alcohol	100-51-6	40	80	

Substances with Community Exposure Limits: Union occupational exposure limit values in accordance with Directive 2000/39/EC (as amended).

Substance	CAS	Limit values		Note
		OEL (mg/m ³)	STEL (mg/m ³)	
No data available.				

DNEL:

3-aminomethyl-3,5,5-trimethylcyclohexylamine (CAS: 2855-13-2)

Exposed group and route of exposure	Duration of exposure	Type of effect	Unit	Value
Workers				

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

Inhalation	Long-term (chronic)	systemic	mg/m ³	-
		local	mg/m ³	0.073
Consumers				
Oral	Long-term (chronic)	systemic	mg/kg bw/d	0.526

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (CAS: 9046-10-0)

Exposed group and route of exposure	Duration of exposure	Type of effect	Unit	Value
Workers				
Inhalation	Long-term (chronic)	systemic	mg/m ³	1.36
Dermal	Long-term (chronic)	systemic	mg/kg bw/d	2.5
Consumers				

Benzyl alcohol (CAS: 100-51-6)

Exposed group and route of exposure	Duration of exposure	Type of effect	Unit	Value
Workers				
Inhalation	Long-term (chronic)	systemic	mg/m ³	22
Dermal	Long-term (chronic)	systemic	mg/kg bw/d	8
Consumers				
Inhalation	Long-term (chronic)	systemic	mg/m ³	5.4
Dermal	Long-term (chronic)	systemic	mg/kg bw/d	4
Oral	Long-term (chronic)	systemic	mg/kg bw/d	4

PNEC:

3-aminomethyl-3,5,5-trimethylcyclohexylamine (CAS: 2855-13-2)

Component of the environment	PNEC	Unit	Value	
Water environment	Freshwater	PNEC _{water, fresh.}	mg/L	0.06
	Freshwater, occasional leakage	PNEC _{water, fresh.}	mg/L	0.23
	Freshwater sediment	PNEC _{sed., fresh.}	mg/kg sediment dw	5.784
	Seawater	PNEC _{water, mar.}	mg/L	0.006
	Marine sediment	PNEC _{sed., mar.}	mg/kg sediment dw	0.578
Microbiological activity	Wastewater treatment plant	PNEC _{sew. treat.}	mg/L	3.18
Terrestrial environment / organisms	Soil	PNEC _{soil}	mg/kg soil dw	1.121

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (CAS: 9046-10-0)

Component of the environment	PNEC	Unit	Value	
Water environment	Freshwater	PNEC _{water, fresh.}	mg/L	0.015
	Freshwater, occasional leakage	PNEC _{water, fresh.}	mg/L	0.15
	Freshwater sediment	PNEC _{sed., fresh.}	mg/kg sediment dw	0.132
	Seawater	PNEC _{water, mar.}	mg/L	0.014
	Marine sediment	PNEC _{sed., mar.}	mg/kg sediment dw	0.125
Microbiological activity	Wastewater treatment plant	PNEC _{sew. treat.}	mg/L	7.5

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

Terrestrial environment / organisms	Soil	PNEC _{soil}	mg/kg _{soil dw}	0.018
Food chain	Predators	PNEC _{oral}	mg/kg _{food}	6.93

Benzyl alcohol (CAS: 100-51-6)

Component of the environment	PNEC	Unit	Value	
Water environment	Freshwater	PNEC _{water, fresh.}	mg/L	1
	Freshwater, occasional leakage	PNEC _{water, fresh.}	mg/L	2.3
	Freshwater sediment	PNEC _{sed., fresh.}	mg/kg _{sediment dw}	5.27
	Seawater	PNEC _{water, mar.}	mg/L	0.1
	Marine sediment	PNEC _{sed., mar.}	mg/kg _{sediment dw}	0.527
Microbiological activity	Wastewater treatment plant	PNEC _{sew. treat.}	mg/L	39
Terrestrial environment / organisms	Soil	PNEC _{soil}	mg/kg _{soil dw}	0.456

8.2 Exposure controls

Technical measures:

Technical measures and appropriate work procedures take precedence over personal protective equipment. Observe the usual hygiene principles. Do not eat, drink, smoke. Before breaks and after work wash your hands with warm water and soap.

Individual protection measures

Respiratory protection:

If the exposure limits are exceeded, when using dust, fog, aerosol, use a suitable filter (type ABEK -EN 14387+A1 - anti-gas and combined filters, type P -EN 143 - particle filters, type FFP3 / FFP2 - EN 149+A1 - Particle-based half masks; EN 142 - mouth masks).

Hand protection:

Protective working gloves (EN 374). Observe the manufacturer's exact instructions, including the time of use. Replace damaged gloves.

Eye / face protection:

Safety glasses with side-plates or facial shields (EN 166).

Skin protection:

Working clothes (EN ISO 13688) and footwear (EN ISO 20347). Protective clothing against liquid chemicals (EN 14605). Protective clothing against chemicals (EN ISO 14325).

Thermal hazards:

No data available.

Environmental exposure controls:

Avoid unnecessary releases into the environment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless
Odour:	No data available.
Odour threshold:	No data available.
pH :	11
Melting point / freezing point (°C):	No data available.
Boiling point or initial boiling point and boiling range (°C):	No data available.
Flash point (°C):	110
Evaporation rate:	No data available.
Flammability (gases, liquids and solids):	No data available.
Lower and upper explosion limit:	No data available.
Vapour pressure (20 °C):	No data available.
Vapour pressure (50 °C):	No data available.

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

Relative vapour density:	No data available.
Density and/or relative density (g/cm ³ , 20 °C):	1
Solubility (20 °C):	No data available.
Partition coefficient n-octanol/water (log value):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Kinematic viscosity:	No data available.
Refractive index (20 °C):	No data available.
Oxidising properties:	No data available.
Explosive properties:	No data available.

9.2 Other information

VOC (%):	0
Dry matter content:	No data available.
Additional information:	

9.2.1 Information with regard to physical hazard classes

The product has no physical hazards.

9.2.2 Other safety characteristics:

mechanical sensitivity:	No data available.
self-accelerating polymerisation temperature:	No data available.
formation of explosible dust/air mixtures:	No data available.
acid/alkaline reserve:	No data available.
evaporation rate	No data available.
miscibility:	No data available.
conductivity:	No data available.
corrosiveness:	No data available.
gas group:	No data available.
redox potential:	No data available.
radical formation potential:	No data available.
photocatalytic properties:	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity	Not expected under proper conditions of use.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	Dangerous reactions are not known.
10.4 Conditions to avoid	Comply with the handling and storage conditions set out in Section 7.
10.5 Incompatible materials	Strong oxidizing agents, strong acids, strong alkalines.
10.6 Hazardous decomposition products	Hazardous decomposition products are not known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
Individual components

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

3-aminomethyl-3,5,5-trimethylcyclohexylamine (CAS: 2855-13-2)

Acute toxicity:

Test type	Results	Exposure	Tested organisms
OECD 401, key study	1 030 mg/kg bw	oral: gavage	rat
OECD 402, key study	> 2 000 mg/kg bw	dermal	rat
OECD 403, key study	>= 1.07 - <= 5.01 mg/L air (analytical) > 5.01 mg/L air (analytical) > 5.01 mg/L air (analytical)	inhalation: aerosol	rat

Serious eye damage / irritation:

Test type	Results	Exposure	Tested organisms
	No data available.		

Skin corrosion / irritation:

Test type	Results	Exposure	Tested organisms
	No data available.		

Respiratory or skin sensitisation:

Test type	Results	Exposure	Tested organisms
	No data available.		

STOT - single exposure:

Test type	Results	Exposure	Tested organisms
	No data available.		

STOT - repeated exposure:

Test type	Results	Exposure	Tested organisms
OECD 408, key study	160 mg/kg bw/day (nominal), LOAEL 59 mg/kg bw/day (actual dose received), NOAEL 62 mg/kg bw/day (actual dose received), NOAEL	oral	rat
supporting study	18 mg/m ³ air, LOEC	inhalation	rat

Carcinogenicity:

Test type	Results	Exposure	Tested organisms
	No data available.		

Germ cell mutagenicity:

Test type	Results	Exposure	Tested organisms
OECD 474, key study	negative	oral: unspecified	mouse

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

Reproductive toxicity:

Test type	Results	Exposure	Tested organisms
OECD 421, supporting study	> 160 mg/kg bw/day, NOAEL > 160 mg/kg bw/day, NOAEL	oral: drinking water	rat

Aspiration hazard:

Test type	Results	Exposure	Tested organisms
	No data available.		

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (CAS: 9046-10-0)

Acute toxicity:

Test type	Results	Exposure	Tested organisms
OECD 401, key study	2 885.3 mg/kg bw, LD50 2 922.1 mg/kg bw, LD50 2 627.2 mg/kg bw, LD50	oral: gavage	rat
OECD 402, key study	2 979.7 mg/kg bw, LD50 2 979.7 mg/kg bw, LD50 2 979.7 mg/kg bw, LD50	dermal	rabbit
OECD 403, key study	> 0.74 mg/L air (nominal), LC50	inhalation: vapour	rat

Serious eye damage / irritation:

Test type	Results	Exposure	Tested organisms
OECD 405, key study	Category 1	Eye	rabbit

Skin corrosion / irritation:

Test type	Results	Exposure	Tested organisms
OECD 404, key study	Category 1C	Skin	rabbit

Respiratory or skin sensitisation:

Test type	Results	Exposure	Tested organisms
	No data available.		

STOT - single exposure:

Test type	Results	Exposure	Tested organisms
	No data available.		

STOT - repeated exposure:

Test type	Results	Exposure	Tested organisms
OECD 407, supporting study	other: ≥ 0.208 , NOEL	oral	rat
OECD 411, key study	250 mg/kg bw/day (nominal), NOAEL 80 mg/kg bw/day (nominal), NOAEL	dermal	rat

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

Carcinogenicity:

Test type	Results	Exposure	Tested organisms
	No data available.		

Germ cell mutagenicity:

Test type	Results	Exposure	Tested organisms
OECD 474, key study	negative	oral: gavage	mouse

Reproductive toxicity:

Test type	Results	Exposure	Tested organisms
OECD 421, key study	30 mg/kg bw/day, NOAEL 10 mg/kg bw/day, NOAEL 30 mg/kg bw/day, NOAEL	dermal	rat

Aspiration hazard:

Test type	Results	Exposure	Tested organisms
	No data available.		

Benzyl alcohol (CAS: 100-51-6)

Acute toxicity:

Test type	Results	Exposure	Tested organisms
key study	1.55 mL/kg bw, LD50 1 mL/kg bw, other:	oral: gavage	rat
weight of evidence	> 2 000 mg/kg bw, LD50	dermal	rabbit
OECD 403, key study	> 4 178 mg/m ³ air, LC50 3 297 mg/m ³ air, other:	inhalation: aerosol	rat

Serious eye damage / irritation:

Test type	Results	Exposure	Tested organisms
other information	moderately irritating	Eye	rabbit

Skin corrosion / irritation:

Test type	Results	Exposure	Tested organisms
other information	moderately irritating	Skin	guinea pig

Respiratory or skin sensitisation:

Test type	Results	Exposure	Tested organisms
weight of evidence	GHS criteria not met	Skin	other:

STOT - single exposure:

Test type	Results	Exposure	Tested organisms
	No data available.		

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

STOT - repeated exposure:

Test type	Results	Exposure	Tested organisms
key study	400 mg/kg bw/day (actual dose received), NOAEL	oral	rat
OECD 412, key study	1 072 mg/m ³ air (analytical), NOAEC	inhalation	rat

Carcinogenicity:

Test type	Results	Exposure	Tested organisms
other information	other: >= 10 - <= 15, other:	in-vitro test	other:

Germ cell mutagenicity:

Test type	Results	Exposure	Tested organisms
other information	other:	oral: feed	Drosophila melanogaster

Reproductive toxicity:

Test type	Results	Exposure	Tested organisms
key study	200 mg/kg bw/day (actual dose received), NOAEL 800 mg/kg bw/day (actual dose received), NOAEL	oral: gavage	mouse

Aspiration hazard:

Test type	Results	Exposure	Tested organisms
	No data available.		

Mixture:

Acute toxicity:	Harmful if swallowed.
Serious eye damage / irritation:	Causes serious eye damage.
Skin corrosion / irritation:	Causes severe skin burns and eye damage.
Respiratory or skin sensitisation:	May cause an allergic skin reaction.
STOT - single exposure:	The product does not meet the criteria for classification.
STOT - repeated exposure:	The product does not meet the criteria for classification.
Carcinogenicity:	The product does not meet the criteria for classification.
Germ cell mutagenicity:	The product does not meet the criteria for classification.
Reproductive toxicity:	The product does not meet the criteria for classification.
Aspiration hazard:	The product does not meet the criteria for classification.

11.2 Information on other hazards Endocrine disrupting properties

This product does not contain endocrine disruptors in a concentration of 0.1% by weight or higher.

Other information: No data available.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

3-aminomethyl-3,5,5-trimethylcyclohexylamine (CAS: 2855-13-2)

Toxicity	Tested organisms	Results	Test type
Acute toxicity to fish	<i>Leuciscus idus</i>	140 mg/L, LC100 / 96 h 110 mg/L, LC50 / 96 h 70 mg/L, LC0 / 96 h	
Acute toxicity to invertebrates	<i>Daphnia magna</i>	66.4 mg/L, EC100 / 48 h 23 mg/L, EC50 / 48 h 8.3 mg/L, NOEC / 48 h 27 mg/L, EC50 / 24 h	OECD 202
Acute toxicity to aquatic algae	<i>Desmodesmus subspicatus</i> (previous name: <i>Scenedesmus subspicatus</i>)	37 mg/L, EC50 / 72 h 3.1 mg/L, EC10 / 72 h > 50 mg/L, EC50 / 72 h 11.2 mg/L, EC10 / 72 h 1.5 mg/L, NOEC / 72 h	

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (CAS: 9046-10-0)

Toxicity	Tested organisms	Results	Test type
Acute toxicity to fish	<i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i>)	> 15 mg/L, EC50 / 96 h 15 mg/L, NOEC / 96 h	OECD 203
Acute toxicity to invertebrates	<i>Daphnia magna</i>	80 mg/L, EC50 / 48 h 18 mg/L, NOEC / 48 h	OECD 202
Acute toxicity to aquatic algae	<i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i>)	15 mg/L, EC50 / 72 h 2.1 mg/L, EC50 / 72 h 1.4 mg/L, EC10 / 72 h 0.32 mg/L, NOEC / 72 h 1 mg/L, LOEC / 72 h	OECD 201

Benzyl alcohol (CAS: 100-51-6)

Toxicity	Tested organisms	Results	Test type
Acute toxicity to fish	<i>Pimephales promelas</i>	770 mg/L, LC50 / 1 h 770 mg/L, LC50 / 24 h 770 mg/L, LC50 / 48 h 460 mg/L, LC50 / 72 h 460 mg/L, LC50 / 96 h	
Acute toxicity to invertebrates	<i>Daphnia magna</i>	230 mg/L, EC50 / 48 h	OECD 202
Acute toxicity to aquatic algae	<i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i>)	770 mg/L, EC50 / 72 h 310 mg/L, NOEC / 72 h 500 mg/L, EC50 / 72 h 310 mg/L, NOEC / 72 h	OECD 201

- 12.2 Persistence and degradability** No data available.
- 12.3 Bioaccumulative potential** No data available.
- 12.4 Mobility in soil** No data available.
- 12.5 Results of PBT and vPvB assessment** This mixture does not contain any substances which are classified as PBT or vPvB
- 12.6 Endocrine disrupting properties** This product does not contain endocrine disruptors in a concentration of 0.1% by weight or higher.
- 12.7 Other adverse effects** No data available.

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Catalogue No. of mixture waste:	08 01 11 waste paint and varnish containing organic solvents or other dangerous substances
Waste codes / waste designations according to LoW:	15 01 11 metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers
Recommended procedure for mixture waste disposal:	No data available.
Recommended procedure for packaging disposal:	Empty containers must be disposed of in accordance with the applicable waste legislation. After perfect cleaning, the packaging can be used as a secondary raw material for the same purpose. Recommended way of disposing of recycling, burning in a hazardous waste incinerator or storing hazardous waste.
Physical / chemical properties that may affect waste treatment method:	No data available.
Sewage disposal-relevant information:	Protect against weathering. Prevent leakage of waste into the water / soil / sewage system. In case of leakage, inform the competent authorities.
Other disposal recommendations:	Dispose of in accordance with applicable legislation.

SECTION 14: Transport information

	Type of transport	Land transport ADR/RID	Sea transport IMDG	Air Transport ICAO / IATA
14.1	UN number or ID number	2735	2735	2735
14.2	UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)
14.3	Transport hazard class(es)	8	8	8
	Classification code	80	-	-
	EmS	-	F-A, S-B	-
	Packaging instructions	P001 / IBC03 / LP01 / R001	P001;LP01 / IBC03	(passanger/cargo) 852 / 856
	Labels	8		
14.4	Packing group	III	III	III

14.5 Environmental hazards No data available.

14.6 Special precautions for user No data available.

14.7 Maritime transport in bulk according to IMO instruments Not specified.

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

Other information

Type of transport	Land transport ADR/RID	Sea transport IMDG	Air Transport ICAO / IATA
Limited quantities:	5 L	5 L	Y841
Excepted quantities:	E1	E1	E1
Transport category:	3	-	-
Tunnel restriction code:	(E)	-	-
Segregation group:	-	SGG18;SG35	-

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1272/2008 (CLP) on classification, labelling and packaging of substances and mixtures, ...
Regulation (EC) No. 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), ...

Applicable national regulations.

15.2 Chemical safety assessment

A chemical safety assessment has been performed.

SECTION 16: Other information

Complete text of all classifications and hazard classes referred to in SECTION 3

Hazard class: Acute Tox. 4 - Acute Toxicity, category 4
Aquatic Chronic 3 - Chronic (long term) aquatic hazard, category 3
Skin Corr. 1B - Skin corrosion, category 1B
Skin Sens. 1 - Skin sensitisation, category 1

H-statements: H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H412 Harmful to aquatic life with long lasting effects.

Abbreviations:

ADN Inland waterways
ADR Accord Dangereuses Route
CAS Chemical Abstracts Service
DNEL Derived no-effect level
EC50 Effect concentration for 50%
EINECS European Inventory of Existing Commercial Chemical Substances
EL50 Effect level for 50%
IATA International Air Transport Association
IC50 Inhibition concentration for 50%
ICAO International Civil Aviation Organization
IL 50 Inhibition load for 50%
IMDG International Maritime Dangerous Goods
LC50 Lethal concentration for 50%
LD50 Lethal dose for 50%
LL50 Lethal load for 50%
LOAEC Lowest observable adverse effect concentration
LOAEL Lowest observable adverse effect level

SAFETY DATA SHEET

according to Regulation No. 1907/2006 (REACH) and
Commission Regulation (EU) 2020/878

Hardener HG 356

Revision: 2.1
Issue date: 2015-07-14
Revision date: 2021-06-10

LOEC	Lowest observable effect concentration
LOEL	Lowest observable effect level
NEL	No effect level
NOAEC	No observable adverse effect concentration
NOAEL	No observable adverse effect level
NOEC	No observable effect concentration
NOEL	No observable effect level
NPK-P	Maximum permissible concentration
OEL	Occupational Exposure Limit (workplace exposure limit - 8 hours / shift)
PBT	Persistent, bioaccumulative and toxic
PEL	Permissible exposure limits
PNEC	Predicted no-effect concentration
RID	Regulations for the International Carriage of Dangerous Goods by Rail
SCL	Specific concentration limits
STEL	Short Term Exposure Limit (short exposure - corresponds to approx. 15 min.)
TT	Toxic threshold
VOC	Volatile organic substances
vPvB	Very persistent and very bioaccumulative
WGK	Hazard classes for water (Wassergefährdungsklassen)

Changes to previous version SDS:

This revision follows the revision: 2019-07-11 and complies with Regulations (EC) No. 1907/2006 (REACH) and No. 1272/2008 (CLP).

Key literature references and sources for data: Regulation (EC) No 1907/2006 of the European Parliament and of the Council (REACH), as amended. Regulation (EC) No 1272/2008 of the European Parliament and of the Council, as amended. Act No. 350/2011 Coll., On chemical substances and chemical mixtures, as amended. Principles for providing first aid during exposure to chemical substances (Assoc. Prof. Daniela Pelclová, MD, CSc., Alexandr Fuchs, MD, CSc., Miroslava Hornychová, MD, CSc., Zdeňka Trávníčková, MD, CSc., Jiřina Fridrichovská, prom. Chem.). Data from the manufacturer of the substance / mixture, if available - data from the registration dossier. (1)

Classification was performed by calculation method.

Instructions for training:

Workers who come into contact with dangerous substances must be aware of the effects of these substances, how they are treated, and protective measures to the extent necessary.

Furthermore, they must be familiar with the first aid principles, with the necessary sanitation procedures and with the procedures for disaster and accident elimination.

The person handling this chemical product must be familiar with the safety rules and the data given in the safety data sheet.

If a hazardous chemical / mixture is classified as corrosive or toxic, workers should be made aware of the Corrosive / Toxic Chemicals / Mixing Rules.

Persons carrying dangerous substances must be familiar with the ADR / RID accident instructions.

Other information:

The above information describes the conditions for safe handling of the product and corresponds to the current knowledge of the manufacturer and serves as instruction for the training of the persons handling the product.

The manufacturer carries guarantee the above-described properties of the product at the recommended use.

The user is responsible for determining the suitability of the product for specific purposes and adapting security measures if such application is contrary to the manufacturer's recommendations.