

Release Spray (Trennspray)

Release Agent

01/19
July 2019

:: CHARACTERISTIC

Release Spray is an all purpose release agent that contains an alternative blowing agent and can be applied onto many materials such as GRP, glass, resopal and silicon rubber moulds. It is sprayed evenly and thinly from a distance of 30 cm and is polished with a soft cloth.

:: AREA OF APPLICATION

All purpose release spray for GRP and silicone moulds when using:

- PUR casting compounds
- PUR foams
- polyester
- epoxy

:: PRODUCT DATA

Material data

Packing	400 ml aerosol can
Colour	whitish transparent
Specific weight	0.65 g/cm ³
Active ingredient content	approx. 2.95 %
Consumption	25-50 g/m ² per coat
Drying time	approx. 15 minutes at 20°C

Shelf life (dry and cool): min. 6 month in the closed original container

:: INSTRUCTIONS FOR USE

Shake can thoroughly before use. Cold cans should be warmed to room temperature before application. The material is sprayed evenly and in a thin coat onto the mould surface from a distance of 20-30 cm. For a very even surface the surface can be polished with a soft cloth.

:: SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Security Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry .

Copyright VOSSCHEMIE

VOSSCHEMIE GMBH

Esinger Steinweg 50
25436 Uetersen
Germany
www.vosschemie.de

SITZ DER GESELLSCHAFT
Uetersen

AMTSGERICHT
Pinneberg – HRB 0265 EL
USt-Id-Nr.: DE134800975
ILN: 41 02870 00000 8

GESCHÄFTSFÜHRER
Dieter Voss, Klaus Voss,
Hans-Joachim Rohde

NIEDERLASSUNGEN
Ratingen, Oschatz, Kolbermoor

Qualitätsmanagement-System
zertifiziert von LLOYD'S nach
der Qualitätssicherungsnorm
DIN EN ISO 9001 : 2015

