

POLY-FLEX TF15

DESCRIPTION

Non-woven fiber made with polyester material of first choice, suitable for processing under pressure and autoclave system for its ventilation characteristics; available in various weights.

DESCRIZIONE

Tessuto non tessuto in agugliato realizzato con materiale in poliestere di prima scelta. Utilizzato per le caratteristiche di ventilazione, può resistere alle lavorazioni sotto pressione sia vacuum che autoclave; è disponibile in varie grammature.

TECHNICAL DATA	
Material	Polyester yarn
Area weight	150 g/m ²
Theorical thickness	1,6 mm
Standard width	1000 - 1270 mm
Max use temperature	180 °C
Roll lenght	100 m
Elongation at room temperature	>50 %
Color	White

CARATTERISTICHE TECNICHE	
Materiale	Fibra poliestere
Peso	150 g/m ²
Spessore teorico	1,6 mm
Altezza standard	1000 - 1270 mm
Temperatura di resistenza	180 °C
Lunghezza rotoli	100 m
Allungamento	>50 %
Colore	Bianco

NOTE

Technical information furnished is based on laboratory findings and believed to be correct. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.

ANGELONI GROUP

Via Abbate Tommaso, 72/A - 30020 Quarto d'Altino (VE) Italy
T. +39 0422 780580 - F. +39 0422 782782
E. info@angelonigroup.com

angelonigroup.com