



TR INDUSTRIES
11022 Vulcan Street
South Gate, CA 90280-0893
Phone 562-923-0838 • Fax 562-861-3475
www.trmoldrelease.com • info@trmoldrelease.com

TR-111 SLURRY WAX RELEASE FLANGES • EDGES • HATS

DESCRIPTION:

A soft white compounded wax based on refined petroleum waxes. Leaves no discoloration to molded parts and contains no silicones.

PRODUCT FEATURES:

- ★ Easy spreading and wipe characteristics
- ★ Provides positive releases, remains soft and ease of removal
- ★ Effectively fills rough surfaces and is PVA compatible
- ★ Good thermal stability with reduced build up

USES:

For all mold flanges, edges and hats in cultured marble, onyx or granite production, tubs, showers, spa fabrication, polymer concrete and general polyester molding applications. Any surface where gloss or cosmetics is not a critical requirement for finished part. Sealer on porous substrates for prototypes and mock-ups or in conjunction with PVA sprayed film.

APPLICATION:

Apply a minimum of two coats with brush or cloth allowing each coat to dry prior to applying additional coats. This provides a base film for initial release. Apply again lightly after first part is pulled and then subsequent coats as needed. Applications will vary dependent on surface conditions, molding cycle, fabrication methods and general shop practices.

PHYSICAL PROPERTIES:

Dry Time: 10-15 minutes at room temperature (75°F/24°C)
Wax Melting or Softening Point: 165°F
Color: White
Density: 0.805
Wt./Gal: 6.71lbs./gal
Flash Point: 120°F (49°C)

STORAGE AND PRECAUTIONS:

Flammable solid, store in a cool dry place and keep in original unopened container. Keep away from spark, open flame or other sources of ignition.

PACKAGING:

Available in gallon 4x1/cases, 5 gallon and 55 gallon drum. Please contact your local TR distributor or call direct.

FOR INDUSTRIAL USE ONLY

The information contained herein is based on tests considered to be reliable and accurate. Because of the wide variance of associated materials and conditions, no warranty is expressed or implied. Each user is encouraged to prepare a test part for their particular application.